


# 屋内照明器具特性




品名	DD-3570-N		
光源	LED15.2W		
実効光束 (器具光束)	1794lm	効率	118.1lm/W



配光曲線図

実光度




1/2照度角

直射水平面照度

単位:Lx

色温度	5000K	
演色評価指数	Ra94	
保守率	良	0.8
	中	0.6
	否	0.54

1/2照度角		
A-A'	61.5	Deg
C-C'	61.5	Deg
最大取付間隔		
A-A'	1.19	H
C-C'	1.19	H



照明率表

	80%				70%				50%				30%				0%
	70%	50%	30%	10%	70%	50%	30%	10%	70%	50%	30%	10%	70%	50%	30%	10%	0%
天井	10%																0%
壁	10%																0%
床	10%																0%
0.60	63	52	45	40	62	52	45	40	60	51	45	40	58	50	44	40	38
0.80	73	62	55	50	71	62	55	50	69	60	55	50	67	59	54	50	48
1.00	80	70	64	59	78	70	63	58	75	68	62	58	73	67	62	58	56
1.25	85	77	71	67	84	76	71	66	81	75	70	66	79	73	69	65	63
1.50	89	82	77	72	88	81	76	72	85	80	75	71	83	78	74	71	69
2.00	95	89	85	81	94	88	84	81	91	87	83	80	89	85	82	79	77
2.50	98	94	90	86	97	93	89	86	94	91	88	85	92	89	86	84	82
3.00	100	96	93	90	99	95	92	90	96	93	91	89	94	92	89	87	85
4.00	103	100	97	95	101	99	96	94	99	97	94	93	97	95	93	91	89
5.00	104	101	99	97	103	100	98	96	100	98	97	95	98	96	95	94	91
7.00	105	104	102	100	104	103	101	99	102	100	99	98	99	98	97	96	94
10.00	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	98	95