


屋内照明器具特性



品名	DD-3512-N		
光源	LED27.0W		
実効光束 (器具光束)	2120lm	効率	78.5lm/W




1/2照度角

直射水平面照度

単位:Lx

器具効率		60.9%
色温度		5000K
演色評価指数		Ra83
保守率	良	0.67
	中	0.63
	否	0.56
1/2照度角		
A—A'	61.0	Deg
C—C'	61.0	Deg
最大取付間隔		
A—A'	1.18	H
C—C'	1.18	H



照 明 率 表

天井	80%				70%				50%				30%				0%
壁	70%	50%	30%	10%	70%	50%	30%	10%	70%	50%	30%	10%	70%	50%	30%	10%	0%
床	10%				10%				10%				10%				0%
0.60	47	42	39	37	46	42	39	37	45	41	39	37	44	41	39	37	36
0.80	51	46	43	41	50	46	43	41	49	45	43	41	48	45	43	41	40
1.00	54	50	47	45	53	49	47	45	52	49	46	45	51	48	46	44	43
1.25	56	53	50	48	56	52	50	48	54	52	49	48	53	51	49	48	47
1.50	58	55	53	51	57	54	52	50	56	54	52	50	55	53	51	50	49
2.00	60	58	56	55	60	58	56	54	58	57	55	54	57	56	54	53	52
2.50	62	60	58	57	61	59	58	57	60	58	57	56	59	57	56	56	54
3.00	63	61	60	59	62	61	60	59	61	60	59	58	60	59	58	57	56
4.00	64	63	62	61	63	62	61	60	62	61	60	59	61	60	59	59	57
5.00	64	63	63	62	64	63	62	61	62	62	61	60	61	61	60	60	58
7.00	65	64	64	63	64	64	63	63	63	62	62	62	62	61	61	61	59
10.00	65	65	65	64	65	64	64	64	63	63	63	62	62	62	62	61	60